



MET system Tutondo EN54 certified

METCUBE

Compact main unit complete with power supply, power amplifiers, monitoring and displaying system for voice evacuation systems.



The system is designed for **connecting up to 8 power amplifier** (zones). Each amplifier drives a single lines speakers (or double lines with optional interface).

Built-in microphone and pre recorded messages that can be activated from the front panel or remotely, with the possibility of sending messages / calls simultaneously on multiple zones.

Analog AUX inputs and digital audio streams.

Monitored 'trigger' inputs for activating events (alarm, evacuation, etc) from the fire alarm central unit or other devices. Main unit complete with **battery charger EN 54-4 certified and 2 batteries compartment.**

The main unit comprises 60W power amplifiers for 100V systems (they can be set as: 3x60W, 1x120W + 1x60W, 1x180W).

Expandable up to 9 x 60W power amplifiers (MET6A1K kit) reaching a total wattage of 540W.

USB interface for connecting mass memory storage devices.

Proprietary bus for paging stations, RS232 serial port, Ethernet port.

EN 54-16 certified.

Power supply: 230V ac and 24V dc.

Dimensions: H310 x W432 x D372 mm (7 RU).

Color: White (Ral 7035)

Weight: 12,5 Kg (main unit with 3 power amplifiers, without batteries)

TUTONDO®

a brand of

A.T.E.C. Srl
Via Nobel, 8
30020 - Noventa di Piave
Venezia - Italy
T +39 0421 65288
T +39 0421 380385
F +39 0421 659017

tutondo@tutondo.com
www.tutondo.com



MET system Tutondo EN54-16 certified



MET8CV4

Main unit complete with monitoring and displaying system for voice evacuation systems.

The system is designed for connecting **4 single lines** (or double lines with optional interface).

Built-in microphone and pre recorded messages that can be activated from the front panel or remotely, with the possibility of sending messages / calls simultaneously on multiple zones.

4 monitored analog inputs + 2 digital audio.

8 monitored 'trigger' inputs for activating events (alarm, evacuation, etc) from the fire alarm central unit or other devices.

Main unit complete with 540W power supply.

USB interface for connecting mass memory storage devices. Proprietary bus for paging stations, RS232 serial port, Ethernet port.

EN 54-16 certified.

Power supply: 230V ac and 24V dc.
Dimensions: H88 x W483 x D330 mm (2 RU). Weight: 6,3 Kg.
Color: black.

MET8CV8

Main unit complete with monitoring and displaying system for voice evacuation systems.

The system is designed for connecting **8 single lines** (or double lines with optional interface).

Built-in microphone and pre recorded messages that can be activated from the front panel or remotely, with the possibility of sending messages / calls simultaneously on multiple zones.

4 monitored analog inputs + 8 unmonitored analog inputs + 2 digital audio.

16 monitored 'trigger' inputs for activating events (alarm, evacuation, etc) from the fire alarm central unit or other devices.

Main unit complete with 540W power supply.

USB interface for connecting mass memory storage devices. Proprietary bus for paging stations, RS232 serial port, Ethernet port.

EN 54-16 certified.

Power supply: 230V ac and 24V dc.
Dimensions: H88 x W430 x D330 mm (2 RU). Weight: 6,3 Kg.
Color: black

TUTONDO®

a brand of

A.T.E.C. Srl
Via Nobel, 8
30020 - Noventa di Piave
Venezia - Italy
T +39 0421 65288
T +39 0421 380385
F +39 0421 659017

tutondo@tutondo.com
www.tutondo.com



Battery charger EN54-4 certified



MET6CB

Monitoring unit
with battery charger of 100Ah for up to **6 power supplies**.

Control unit and status display of up to **6 power supplies**, charger for lead-acid type batteries, up to 100Ah complete with probe for temperature control of the charge.

Rated operating voltage 24V dc, 32A maximum capacity for each output, total controlled power 2400W. RS232 port.

EN 54-4 certified.

19" rack standard, 2 units (recommended guides Tutondo GRPW2).

Main power supply: 230V ac.

Dimensions: W483 x D380 x H88 mm.

Weight: 5,3 Kg

Color: Black

TUTONDO®

a brand of

A.T.E.C. Srl
Via Nobel, 8
30020 - Noventa di Piave
Venezia - Italy
T +39 0421 65288
T +39 0421 380385
F +39 0421 659017

tutondo@tutondo.com
www.tutondo.com